



## Company Introduction

QINGDAO SUNSTAR RUBBER CO.,LTD is located in Qingdao, China, which specializes in the tyre R&D, tyre manufacture and international trade.

Our company primarily manufactures various models of tyres, including TBR,PCR,OTR,AGR, INDUSTRIAL TYRES and TBB TYRES, inner tubes, Flap,Filters and relative wheels etc.

SUNSTAR RUBBER company's products are in great demand in Southeast Asia, Middle East, Africa, South America, Europe,etc.The company emphasize a lot on product quality,which has passed ISO9001,DOT,ECE,GCC,CCC,SONCAP,SMARTWAY etc.

Our company has professional R & D, sales and after-sales team,We will stick to the " Innovation, Pragmatic, Integrity, Win - Win " spirit of enterprise and sincerely provide our clients with qualified products and thoughtful services. We are willing to establish a long-term cooperation relations with more domestic and abroad business partners and friends.



Size	For Mix Road	For Highway	For Off The Road
6.50R16LT	AM868		
7.00R16LT	AM868		
7.50R16LT	AM868	AM628	
8.25R16LT	AM868	AM628	
8.25R20	AM868		
9.00R20	AM868	AM603	AM696
10.00R20	AM868	AM626 AM603 AM628	AM666 AM696
11.00R20	AM868	AM603 AM628	AM666 AM696
12.00R20	AM868	AM603 AM628	AM666 AM696
11R22.5	AM868	AM818 AM659 AM687 AM636 AM626	
12R22.5	AM868	AM818 AM598 AM688	
13R22.5	AM868	AM687	AM666
385/65R22.5		AM870 AM685	
295/75R22.5		AM818 AM659	
295/80R22.5	AM868	AM818 AM598 AM688 AM687	AM666 AM608
315/80R22.5	AM868	AM818 AM598 AM896 AM688 AM687 AM606	
12.00R24	AM698 AM868	AM687 AM603	AM616
11R24.5		AM818 AM659 AM636 AM626	
285/75R24.5		AM818 AM659	





## AM868

- Mixed rib pattern
- Good ground grasping capability
- Sideslip resistance
- Pitch pattern designed
- Low noise, suitable for all kinds of the roads of the town

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (PSI)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
8.25R20	14	6.50	136/134K	830	2240	2120	236	974	13.5
	16	6.50	139/137K	930	2430	2300	236	974	13.5
9.00R20	16	7.00	144/142K	900	2800	2650	259	1019	15.5
10.00R20	18	7.50	149/146L	930	3250	3000	278	1054	17
11.00R20	18	8.00	152/149L	930	3550	3250	293	1085	17
12.00R20	18	8.50	154/151L	830	3750	3450	315	1125	17.5
	20	8.50	156/153K	900	4000	3650	315	1125	17.5
12.00R24	20	8.50	160/157K	900	4500	4125	315	1226	16
6.50R16LT	12	5.50F	110/105L	670	1060	925	185	750	12
7.00R16LT	12	5.50F	115/110L	670	1215	1060	200	775	12
7.50R16LT	14	5.50F	118/114L	770	1320	1180	200	775	12
8.25R16LT	16	6.00G	122/118L	770	1500	1320	215	805	12
8.25R16LT	16	6.50H	128/124L	770	1800	1600	235	855	14
11R22.5	16	8.25	146/143L	830	3000	2725	279	1054	15
12R22.5	18	9.00	152/149M	850	3550	3150	300	1084	17.5
13R22.5	18	9.75	154/151K	875	4000	3350	320	1124	21.5
295/80R22.5	18	9.00	152/148M	850	3550	3150	298	1044	14.5
315/80R22.5	20	9.00	157/154L	900	4125	3750	312	1076	17.5



## AM818

- Applied to steering wheel on good condition road.
- With excellent tread abrasion property and low heat generation, adapts to long distance and high speed running on common and good condition.
- Rib pattern with special delicate grooves, endows the tyre with excellent performance in driving straightly and avoiding partial grinding.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (PSI)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
315/80R22.5	20	9.00	157/154L	900	4125	3750	312	1076	16
11R22.5	16	8.25	146/143L	830	3000	2725	279	1054	16
12R22.5	18	9.00	152/149M	930	3550	3250	300	1085	16.5
295/80R22.5	18	9.00	152/149L	900	3550	3250	298	1044	16
285/75R24.5	16	8.25	147/144L	830	3075	2800	283	1050	15
295/75R22.5	16	9.00	146/143L	830	3000	2725	298	1014	15
11R24.5	16	8.20	149/146L	830	3250	3000	279	1104	15



## AM598

- High abrasion, well resistance to impact, well sideslip resistance and heat dispersion
- superior stability in high-speed running.
- Suitable for highway and ordinary grade pavement.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (PSI)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
12R22.5	18PR	9.00	152/148M	850	3550	3150	300	1084	14.5
295/80R22.5	18PR	9.00	152/148M	850	3550	3150	298	1044	15
315/80R22.5	20PR	9.00	156/150M	850	4000	3350	312	1076	14.5



## AM896

- Excellent Lateral spreads slippery resistance
- low rolling resistance and noise
- superior stability in high-speed running.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (PSI)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
315/80R22.5	20	9.00	156/150M	850	4000	3350	312	1076	14.50



## AM836

- High abraion,well eccentric wear resistance,
- well heat dispersion and resistance to impact
- Superior stability in high-speed running.
- Suitable for highway and ordinary grade pavement.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX.LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
11R22.5	16PR	8.25	146/143M	830	3000	2725	279	1050	14.5
11R24.5	16PR	8.25	149/146M	830	3250	3000	279	1104	14.5



## AM688

- Good abrasion outure resistance
- Good loading capability
- Good grasping performance
- Suitable for rough road and high way

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX.LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
12R22.5	16	9.00	152/149M	930	3550	3250	300	1085	23
295/80R22.5	18	9.00	152/149L	900	3550	3250	298	1050	23
315/80R22.5	20	9.00	156/153L	850	4000	3350	312	1082	23



## AM606

- Medium short load tire,The massive directed-drive pattern
- Truck used tyre,applied to heavy-duty load, short distance, medium speed running on mixed condition road

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX.LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
315/80R22.5	20	9.00	157/154L	900	4125	3750	298	1082	18



## AM687

- Good mileage potential
- Excellent resistance to damage and punctures on/off road
- Good on/off road grip

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX.LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
295/80R22.5	18	9.00	152/148M	850	3550	3150	298	1044	21.5
315/80R22.5	20	9.00	156/153M	850	4000	3350	312	1076	21.5
11R22.5	16	8.25	146/143M	825	3000	2725	279	1054	20
13R22.5	18	9.75	154/151K	875	4000	3350	320	1124	21.5
1200R24	20	8.5	160/157K	900	4500	4125	279	1054	16



## AM666

- High speed
- High loading capability
- Good sideslip and mud slip resistance
- Suitable for guiding and all use

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX.LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
10.00R20	18	7.5	149/146L	930	3250	3000	278	1054	20
11.00R20	18	8	149/146L	930	3550	3250	293	1085	20.5
12.00R20	18	8.50	156/153L	830	3750	3450	315	1125	22
	20	8.50	156/153K	900	4000	3650	315	1125	22
295/80R22.5	16	9.00	150/147M	830	3350	3075	298	1044	22
	18	9.00	152/149L	850	3550	3250	298	1044	22
13R22.5	18	9.75	154/151K	875	4000	3350	320	1124	22



## AM608

- Special mining tyre, suitable for transportation on a variety of complex road.
- Excellent ground grip and superior traction performance.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
295/80R22.5	18	9.00	152/149L	900	3550	3250	298	1050	18



## AM659

- Better gripping performance both on snowy and muddy road.
- Better tracking and abrasion resistance, lower traffic noise ensure longer service life

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
285/75R24.5	14	8.25	144/141M	760	2800	2575	283	1056	22.5
295/75R22.5	14	9.00	144/141M	760	2800	2575	298	1020	22
11R22.5	16	8.25	146/143L	830	3000	2725	279	1065	22
11R24.5	14	8.25	146/143M	720	3000	2725	279	1116	22



## AM626

- Superior driving and braking performance, high abrasion, low heating generation,
- Superior adhesion, excellent lateral slips slippery resistance, low noise, reducing vehicle parts loss.
- Suitable for highway and ordinary grade pavement.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
10.00R20	18PR	7.50	149/146L	930	3250	3000	278	1054	17
11R22.5	16PR	8.25	146/143M	830	3000	2725	279	1050	20.5
11R24.5	16PR	8.25	149/146M	830	3250	3000	279	1104	20.5



## AM698

- High powered mixed pattern
- High loading capacity
- Quasi-sovereign tread pattern
- Integrative shoulder pattern
- Suitable for all kinds of the roads

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
12.00R24	20	8.50	160/157K	900	4500	4125	315	1226	16



## AM616

- Wide and thick blocks, Extra deep tread depth, offer excellent traction
- Designed with strong structure, Good load capacity and long service life.
- Good anti-Puncture attributes
- Suitable to mine and moun and mountain roads

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
12.00R24	20	8.50	160/157K	900	4500	4125	315	1226	21



## AM685

- Mixed rib pattern
- Good ground grasping capability
- Sideslip resistance
- Pitch pattern designed
- Low noise, suitable for all kinds of the roads of the town

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
385/65R22.5	20	11.75	160K	830	4500	4125	389	1072	16



## AM870

- Mixed rib pattern
- Good ground grasping capability
- Sideslip resistance
- Pitch pattern designed
- Low noise
- Suitable for all kinds of the roads of the town

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
385/65R22.5	20	11.75	160K	830	4500	4125	389	1072	16.5



## AM603

- Superior driving and braking performance, high abrasion, high tear and cut resistance.
- Superior adhesion, well resistance to impact, well heat dispersion, and low heating generation.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
9.00R20	16	7.00	144/142K	900	2800	2650	259	1019	14.5
10.00R20	18	7.50	149/146L	930	3250	3000	278	1054	16.0
11.00R20	18	8.00	152/149L	930	3550	3250	293	1085	16.5
12.00R20	18	8.50	154/151L	830	3750	3450	315	1125	17.0
12.00R24	20	8.50	160/157K	900	4500	4125	315	1226	15.5



## AM628

- Superior anti-irregular wearing performance and stability in running, well heat dispersion.
- Suitable for highway speed and heavy roads
- Excellent traction and adhesion

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
7.50R16LT	14	6.00G	122/118L	770	1500	1320	215	805	14.5
8.25R16LT	16	6.50H	128/124L	770	1800	1600	235	855	15.5
10.00R20	18	7.50	149/146L	930	3250	3000	278	1054	19.0
11.00R20	18	8.00	152/149L	930	3550	3250	293	1085	20.0
12.00R20	18	8.50	154/151L	830	3750	3450	315	1125	21.0
12.00R20	20	8.50	156/153K	900	4000	3650	315	1125	21.0



## AM696

- Superior traction and adhesion, excellent lateral spreads slippery resistance high tear resistance, high abrasion, well loading capacity.

SIZE	PR	STANDARD RIM	LOAD INDEX	PRESSURE (KPA)	MAX. LOAD		S.W (MM)	O.D (MM)	TREAD DEPTH (MM)
					SINGLE	DUAL			
9.00R20	16	7.00	144/142K	900	2800	2650	259	1019	22.50
10.00R20	18	7.50	149/146L	930	3250	3000	278	1054	24.50
11.00R20	18	8.00	152/149L	930	3550	3250	293	1085	24.50
12.00R20	20	8.5	156/153K	830	3750	3450	315	1125	25.00